



4048PS-ATV 12.5 cu ft POLY SWIVEL ATV DUMP CART

U.S. Patent No. 8,496,298



READ AND FOLLOW ALL SAFETY RULES AND OPERATING INSTRUCTIONS BEFORE USING THIS EQUIPMENT



This is the safety alert symbol. It is used to alert you to potential personal injury hazards. Obey all safety messages that follow this symbol to avoid possible injury or death.

Read and understand all safety rules and operating instructions before using this ATV/UTV attachment.

Follow all safety rules and operating instructions provided by your vehicle's manufacturer when using attachment.

Never allow children or untrained persons to operate vehicle or attachment.

Do not exceed the vehicle manufacturer's towed weight limit.

Reduce vehicle speed and allow extra stopping distance when towing heavy loads.

Reduce vehicle speed and towed weight when operating on slopes.

Operate up and down slopes, never across the face of slopes.

Do not carry passengers on vehicle or attachment.

Avoid sudden turns or maneuvers.

Do not tow attachment on public roadways.

Do not remove warning decals from product.


Check product for worn, loose, or damaged parts before each use. If any damage is present, repair the product before using.

Check product for loose or missing fasteners before each use. Tighten or replace fasteners as needed before using.


Do not exceed vehicle speed of 20 miles per hour when towing Dump Cart.

Do not exceed Dump Cart rated weight capacity of 1250 pounds.


Carton Contents



Assembly Instructions



Assembly Instructions



Before Using Dump Cart:

- 1. Apply lithium grease to wheels using grease gun until grease can be seen squeezing out from both sides of the wheel.
- 2. Check tire pressure and inflate to 24 psi if needed.
- 3. Read all Safety Rules found on page 1.

How to Use Dump Cart:

- 1. Attach Dump Cart to your ATV or UTV.
- 2. Do not exceed 1250 pounds when loading material into the cart body.
- 3. Distribute the weight of the load as evenly as possible in the cart body for best handling.
- 4. When hauling heavy loads, verify that your vehicle has adequate towing and braking capacity.
- 5. Do not exceed 20 miles per hour when towing Dump Cart.


How to Empty Dump Cart:

- 1. Step down the foot pedal to release the latch mechanism.
- 2. Lift the body and swivel as desired to guide the material to preferred location.
- 3. Lift the body entirely and empty material.
- 4. Lower the body and guide the latch into the drawbar and relatch.

Periodic Maintenance:

- Tighten fasteners as needed before each use
- Check tire pressure before each use
- Grease wheels annually

Do-It-Yourself Accessories



Warranty

If this product fails due to a defect in material or workmanship within THREE YEARS from the date of purchase, we will at our option repair or replace it free of charge. This warranty excludes tires and wheels, which are expendable and become worn during normal use.

This warranty does not cover:

- Repairs necessary because of operator abuse or negligence.
- Equipment used for commercial or rental purposes.
- Paint that is worn or faded due to normal use or exposure.

To arrange for product repair call 1-800-652-2321, or return this product to place of purchase for replacement.

This warranty gives you specific legal rights, and you may also have other rights which may vary from state to state. This warranty applies only while this product is in use in the United States.

In the space below record the purchase date of your Dump Cart.

Model Number _ 4048PS-ATV

Purchase Date


Keep this Owner's Manual and your receipt in a safe place for future reference.

After the three year warranty period all replacement parts may be ordered by calling *1-800-652-2321*.

When ordering replacement parts, always give the following information:

- Product <u>12.5 cu ft POLY SWIVEL ATV DUMP CART</u>
- Model Number <u>4048PS-ATV</u>
- Part Number ______
- Part Description ______

Exploded View



REPLACEMENT PARTS ORDERING

DRAWBAR

LOCKNUT, 3/8-16

OHIO STEEL INDUSTRIES 1-800-652-2321

KIT, 1" WHEEL BEARINGS

Repair Kits

KIT	KIT NUMBER	PART NUMBER		QTY
HARDWARE BOLT BAG	6000761	3000511	HEX BOLT, 3/8-16 X 1"	4
		6000370	HEX BOLT, 3/8-16 X 3-1/2"	2
		300077	WASHER, 3/8" SAE	8
		3000618	HEX NUT, 3/8-16 NYLOC	6
		3000528	HEX BOLT, 5/16-18 X 1-1/2"	4
		6000373	HEX BOLT, 5/16-18 X 3"	8
		6000409	LOCKWASHER, 5/16"	12
		6000410	HEX NUT, 5/16-18	12
		6000371	PIN, 1/2" X 2-13/32"	1
		6000372	HAIRPIN COTTER, 0.080" X 1-9/16"	2
		3000811	CLEVIS PIN, 1/4" X 1-1/2"	2
		3000812	HAIRPIN COTTER, 0.080" X 1-3/16"	2
		300076	WASHER, 1" SAE	4
		300087	COTTER PIN, 3/16" X 1-1/2"	2
		300121	SPACER, 1" X 1.375"	2
1" WHEEL BEARING KIT	6000818	6000814	1" BEARING RETAINER	4
		6000816	1" ROLLER BEARING	2
DRAWBAR ASSEMBLY	6000323	300055	HEX BOLT, 3/8-16 X 3"	1
		300061	HEX NUT, 3/8-16 C-LOCK	4
		300075	WASHER, 1/2" USS	1
		3000720	WASHER, 3/8" USS	1
		6000305	FOOT PEDAL	1
		6000309	LATCH	1
		6000321	CLEVIS, SWIVEL	1
		6000324	BEARING	2
		6000325	SPRING, LATCH	2
		6000368	WASHER, SPRING	1
		6000369	SHOULDER BOLT, 1/2" X 3/8"	1
		6000370	HEX BOLT, 3/8-16 X 3-1/2"	2
		6000322	FORMED DRAWBAR	1

Before you call...

Please email our customer service team at cs@ohiosteel.com with:

- 1. A description of the issue you are having
- 2. Photos of the issue that include an overall view and detailed view from multiple angles
- 3. If applicable, a short video showing the issue

If you believe this is a warranty related issue please see the warranty page in this manual

Replacement Parts:

If you are ordering replacement part(s) for your product, please note that some parts are only available as a repair kit.

- 1. First locate the part on the Exploded View page (page 8)
- 2. Take note of the part number
- 3. If the part number is on the Repair Kits page, use the kit number to order your replacement parts
- 4. If the part number is not on the Repair Kits page, use the part number to order your replacement part

You can place your parts order online at ohiosteel.com/partsstore

You can also reach our Customer Service Department at 1-800-652-2321



www.OHIOSTEEL.com

(800) 652-2321